### SAFETY DATA SHEET

# CONTE A PARIS FIXATIF POUR FUSAINS ET PASTELS AEROSOL / FIXATIVE FOR CHARCOALS AND PASTELS SPRAY

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name CONTE A PARIS FIXATIF POUR FUSAINS ET PASTELS AEROSOL / FIXATIVE FOR

CHARCOALS AND PASTELS SPRAY

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Fixing pastel, chalk, charcoal and pencil drawings.

# 1.3. Details of the supplier of the safety data sheet

**Supplier** ColArt International Holdings Ltd.

The Studio Building 21 Evesham Street

London W11 4AJ United Kingdom +44 (0)208 424 3200 R.Enquiries@colart.co.uk

Contact person Regulatory Manager

Manufacturer ColArt International SA

5 Rue Rene Panhard

Z.I.Nord

72021 Le Mans Cedex 2 +33 2 43 83 83 00

### 1.4. Emergency telephone number

Emergency telephone +44 (0)208 424 3200 This telephone number is available during office hours only 09:00 to

17:00 GMT Language English.

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Classification

## Physical hazards

Aerosol 1 - H222, H229

### Health hazards

Eye Irrit. 2 - H319 STOT SE 3 - H336

## **Environmental hazards**

Not Classified

### Classification (67/548/EEC or 1999/45/EC)

Xi;R36. F+;R12. R67.

# 2.2. Label elements

### **Pictogram**





Signal word

Danger

### **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with national regulations.

### Contains PROPAN-2-OL, BUTANONE

## Supplementary precautionary statements

P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P337 If eye irritation persists:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

### 2.3. Other hazards

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

ETHANOL 30-60%

CAS number: 64-17-5 EC number: 200-578-6 REACH registration number: 01-2119457610-43-xxxx

Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11

Eye Irrit. 2 - H319

BUTANE 10-30%

**CAS number:** 106-97-8 **EC number:** 203-448-7

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Gas 1 - H220 F+;R12

Press. Gas

PROPAN-2-OL 10-30%

CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-2119457558-25-xxxx

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xi;R36 R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

BUTANONE 5-10%

CAS number: 78-93-3 EC number: 201-159-0 REACH registration number: 01-2119457290-43-xxxx

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Lig. 2 - H225 F;R11 Xi;R36 R66 R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

# SECTION 4: First aid measures

## 4.1. Description of first aid measures

# General information

Move affected person to fresh air at once. Get medical attention if any discomfort continues.

### Inhalation

Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.

### Ingestion

Rinse mouth thoroughly with water.

### Skin contact

Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

# Eye contact

Remove any contact lenses and open eyelids wide apart. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## 4.2. Most important symptoms and effects, both acute and delayed

### Inhalation

Vapours may cause headache, fatigue, dizziness and nausea.

### Ingestion

May cause stomach pain or vomiting.

### Skin contact

Prolonged skin contact may cause redness and irritation.

# Eye contact

Prolonged contact may cause redness and/or tearing.

### 4.3. Indication of any immediate medical attention and special treatment needed

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

### Suitable extinguishing media

Extinguish with the following media: Foam. Carbon dioxide (CO2). Powder. Water spray.

### 5.2. Special hazards arising from the substance or mixture

### Specific hazards

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2). Nitrous gases (NOx). Containers can burst violently or explode when heated, due to excessive pressure build-up. Extremely flammable.

### 5.3. Advice for firefighters

## Protective actions during firefighting

Avoid breathing fire gases or vapours. Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Environmental precautions

### **Environmental precautions**

Do not discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

### Methods for cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. If leakage cannot be stopped, evacuate area.

### 6.4. Reference to other sections

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

### Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### 7.2. Conditions for safe storage, including any incompatibilities

### Storage precautions

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### 7.3. Specific end use(s)

# Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure Controls/personal protection

# 8.1. Control parameters

## Occupational exposure limits

### **ETHANOL**

Long-term exposure limit (8-hour TWA): OES 1000 ppm 1920 mg/m3

Short-term exposure limit (15-minute): OES

#### BUTANE

Long-term exposure limit (8-hour TWA): OES 600 ppm 1450 mg/m3 Short-term exposure limit (15-minute): OES 750 ppm 1810 mg/m3

### PROPAN-2-OL

Long-term exposure limit (8-hour TWA): OES 400 ppm 999 mg/m3 Short-term exposure limit (15-minute): OES 500 ppm 1250 mg/m3

### **BUTANONE**

Long-term exposure limit (8-hour TWA): OES 200 ppm 600 mg/m3 Short-term exposure limit (15-minute): OES 300 ppm 899 mg/m3

# Zinc Oxide: dust Zinc Oxide: dust

### Ingredient comments

OES = Occupational Exposure Standard.

### 8.2. Exposure controls

### Protective equipment





## Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

## Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

# Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Use appropriate skin cream to prevent drying of skin.

## Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

### **SECTION 9: Physical and Chemical Properties**

### 9.1. Information on basic physical and chemical properties

### **Appearance**

Clear liquid.

### Odour

Solvent.

## Melting point

<-20°C

### Initial boiling point and range

78 - 79.6°C @ 760 mm Hg

### Flash point

11°C CC (Closed cup).

### **Evaporation rate**

3.7 BuAc=1

### Upper/lower flammability or explosive limits

: 1.8

### Vapour pressure

853000 Pa @ °C

### Vapour density

Not applicable.

### Relative density

0.791 @ °C

### Solubility(ies)

Soluble in water.

## Auto-ignition temperature

365°C

## Viscosity

1 mPas @ 20°C

### 9.2. Other information

## Volatility

97.4

### Volatile organic compound

This product contains a maximum VOC content of 721 .

# SECTION 10: Stability and reactivity

### 10.1. Reactivity

## 10.2. Chemical stability

### Stability

Stable at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Not known.

## 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.

# 10.5. Incompatible materials

### Materials to avoid

Plastic

# 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### Acute toxicity - oral

## Acute toxicity oral (LD₅ mg/kg)

4,844

### Acute toxicity - dermal

Not determined.

## Acute toxicity - inhalation

Not determined.

### Inhalation

May cause respiratory system irritation. Prolonged inhalation of high concentrations may damage respiratory system.

### Skin contact

Product has a defatting effect on skin. May cause skin irritation/eczema.

## Eye contact

Irritating to eyes.

# **SECTION 12: Ecological Information**

## **Ecotoxicity**

The product is not expected to be hazardous to the environment.

## 12.1. Toxicity

### Acute toxicity - fish

Not determined.

# Acute toxicity - aquatic invertebrates

Not determined.

# Acute toxicity - aquatic plants

Not determined.

## Acute toxicity - microorganisms

Not determined.

## 12.2. Persistence and degradability

## Persistence and degradability

The degradability of the product is not known.

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

# Adsorption/desorption coefficient

Not available.

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

### Disposal methods

Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## **SECTION 14: Transport information**

## 14.1. UN number

**UN No. (ADR/RID)** 1950 **UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

## 14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

AEROSOLS, FLAMMABLE

Proper shipping name

(IMDG)

AEROSOLS, FLAMMABLE

Proper shipping name

(ICAO)

AEROSOLS, FLAMMABLE

Proper shipping name (ADN) AEROSOLS, FLAMMABLE

## 14.3. Transport hazard class(es)

ADR/RID label 2.1
IMDG class 2.1
ICAO class/division 2.1

### Transport labels



### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

## Environmentally hazardous substance/marine pollutant

No.

## 14.6. Special precautions for user

Tunnel restriction code (D)

# 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU legislation**

Dangerous Substances Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### Water hazard classification

WGK 1

## 15.2. Chemical safety assessment

# **SECTION 16: Other information**

Revision date 13/03/2015

Revision 1

Supersedes date 10/11/2012

Risk phrases in full

R11 Highly flammable

R12 Extremely flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

### Hazard statements in full

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: may burst if heated

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.