SAFETY DATA SHEET

LIQUITEX PALETTE WETTING SPRAY / HUMIDIFICATEUR POUR PEINTURE ACRYLIQUE

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name LIQUITEX PALETTE WETTING SPRAY / HUMIDIFICATEUR POUR PEINTURE

ACRYLIQUE

Product number D012158

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Medium for Acrylic Painting

1.3. Details of the supplier of the safety data sheet

Supplier ColArt International Holdings Ltd.

The Studio Building 21 Evesham Street

London W11 4AJ United Kingdom +44 (0)208 424 3200 R.Enquiries@colart.co.uk

Contact person Regulatory Manager

Manufacturer ColArt International SA

5 Rue Rene Panhard

Z.I .Nord

72021 Le Mans Cedex 2 +33 2 43 83 83 00

1.4. Emergency telephone number

Emergency telephone +44 (0)208 424 3200 This telephone number is available during office hours only 09:00 to

17:00 GMT Language English.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

LIQUITEX PALETTE WETTING SPRAY / HUMIDIFICATEUR POUR PEINTURE ACRYLIQUE

mono propylene glycol 1-5%

CAS number: 57-55-6 EC number: 200-338-0 REACH registration number: 01-

2119456809-23-xxxx

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments

Any hazardous ingredients are below classification limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any

discomfort continues.

Skin contact Remove affected person from source of contamination. Get medical attention if irritation

persists after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.

Hazardous combustion

products

No known hazardous decomposition products.

5.3. Advice for firefighters

Protective actions during

firefighting

Not relevant.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into

containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering

drains, sewers or watercourses.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

LIQUITEX PALETTE WETTING SPRAY / HUMIDIFICATEUR POUR PEINTURE ACRYLIQUE

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container. Store at moderate temperatures in dry, well ventilated

area.

Storage class Unspecified storage.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

mono propylene glycol

Long-term exposure limit (8-hour TWA): WEL 150 ppm 474 mg/m³ total vapour and particulates

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

ZINC CHLORIDE

Long-term exposure limit (8-hour TWA): OES 1 mg/m³ Short-term exposure limit (15-minute): OES 2 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering

controls

No specific ventilation requirements.

eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

Hand protection No specific hand protection noted.

Other skin and body

protection

No specific recommendations

Hygiene measures Wash hands at the end of each work shift and before eating, smoking and using the toilet.

Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to

prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid

Colour Colourless.

Odour Characteristic.

pH pH (concentrated solution): 9-10

Initial boiling point and range > 100°C @ 760 mm Hg

Vapour density > 1

Relative density 1 @ 20°C

Solubility(ies) Miscible with water

9.2. Other information

SECTION 10: Stability and reactivity

LIQUITEX PALETTE WETTING SPRAY / HUMIDIFICATEUR POUR PEINTURE ACRYLIQUE

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time. Avoid freezing.

10.5. Incompatible materials

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

General information This product has low toxicity. Only large quantities are likely to have adverse effects on

human health.

Ingestion May cause discomfort if swallowed.

Skin contact Slightly irritating.

Eye contact Irritating to eyes.

Acute and chronic health

hazards

No specific health hazards known.

Route of entry Skin and/or eye contact.

Medical symptoms Irritation of eyes and mucous membranes.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

LIQUITEX PALETTE WETTING SPRAY / HUMIDIFICATEUR POUR PEINTURE ACRYLIQUE

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

Waste class 08 01 12 waste paint and varnish other than those mentioned in 08 01 11

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Dangerous Substances Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

System of specific information relating to Dangerous Preparations. 2001/58/EC.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 31/07/2015

Revision 3

Supersedes date 24/03/2015

LIQUITEX PALETTE WETTING SPRAY / HUMIDIFICATEUR POUR PEINTURE ACRYLIQUE

Risk phrases in full Not classified.

R22 Harmful if swallowed. R35 Causes severe burns.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.