

Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

revision 02.12.2019 (GB) Version 7.6

Silikon-Öl-Spray

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Silikon-Öl-Spray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Lubricant

1.3. Details of the supplier of the safety data sheet

Manufacturer F.W.Klever

Hauptstraße 20, D-84168 Aham

Phone +49 (0) 8744 96 99 10, Fax + 49 (0) 8744 96 99 96

E-Mail info@ballistol.de Internet www.ballistol.de

Advice Qualitätssicherung

Phone +49 (0) 8744 96 99 30 E-mail (competent person):

info@ballistol.de

1.4. Emergency telephone number

Emergency advice Dr.Zettler (Werktags von 8.00 Uhr bis 16.00 Uhr) oder

Giftnotrufzentrale 022819240 Phone +49 (0) 8744 96 99 30

Classification procedure

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard
categories

Aerosol 1
Skin Irrit. 2
STOT SE 3
Aquatic Chronic 2

Hazard
Statements
H222, H229
H315
H336
H411

Hazard statements for physical hazards

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Hazard statements for health hazards
H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Hazard statements for environmental hazards

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH) revision 02.12.20

02.12.2019 (GB) Version 7.6

Silikon-Öl-Spray

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]







GHS02

GHS07

GHS09

Signal word

Danger

Hazard statements for physical hazards

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Hazard statements for health hazards H315 Causes skin irritation.

H336 Causes skin irritation.

May cause drowsiness or dizziness.

Hazard statements for environmental hazards

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

General

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

Response

P302 + P352 IF ON SKIN: Wash with plenty of water/....

Storage

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container to recycling

Hazardous ingredients for labeling

2-Methylpentan (107-83-5)

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Hazardous ingredients

CAS No EC No Name [% Classification according to

weight] Regulation (EC) No 1272/2008 [CLP/

GHS]

74-98-6 200-827-9 propane <15 Flam. Gas 1, H220 / Press. Gas



revision 02.12.2

02.12.2019 (GB) Version 7.6

Silikon-Öl-Spray

Hazardous ingredients (continued)

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/ GHS]
106-97-8	203-448-7	butane	< 15	Flam. Gas 1, H220 / Press. Gas
107-83-5	203-523-4	hexane (containing < 5 % n-hexane (203-777-6))	> 25	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Skin Irrit. 2, H315 / STOT SE 3, H336 / Aquatic Chronic 2, H411

Additional advice

Aerosol: Propellant propane/butane gas

Labelling for contents according to regulation (EC) No 648/2004, annex VII

Food Pure silicone oil in solvent

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

If troubles appear bring to a medical treatment

Rinse out mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media Suitable extinguishing media

Foam

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet



revision 02.12.2019 (GB) Version 7.6

Silikon-Öl-Spray

5.2. Special hazards arising from the substance or mixture

Carbon monoxid (CO)
Carbon dixide (CO2)
Vapours may form explosive mixtures with air

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply (isolated).

Additional information

Cool endangered containers with water spray jet. Heating causes rise in pressure with risk of bursting

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures For non-emergency personnel

Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.
Do not breath vapour or spray.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up residues with absorbent material (e.g. sand, sawdust, general-purpose binder).

6.4. Reference to other sections

No information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Do not spray into flames or ignition sources

General protective measures

Avoid contact with eyes and skin Do not inhale aerosols

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Storing of food in workroom forbidden.

Wash hands before breaks and after work.

Use barrier skin cream.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Protect aerosols from temperatures exceeding 50°C

Do not open with force or incinerate, even when empty



revision 02.12.2019

02.12.2019 (GB) Version 7.6

Silikon-Öl-Spray

7.2. Conditions for safe storage, including any incompatibilities Further information on storage conditions

Protect from extreme heat and cold.

Keep cool.

Storage group 2B

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

The following applies to propane in general: If the concentration is exceeded, closed-circuit breathing apparatures must be used

Use filter apparatus type AX, identification colour brown according to EN 371

Hand protection

Gloves (solvent-resistant)

Eye protection

With demand: protective glasses

Other protection measures

protective clothing

Limitation and surveillance of the environment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Colour

Odour

aerosol

colourless, clear

solvent-like

Odour threshold not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling range	ca. 48 - 70 °C				Details refer to the active agent (without consideration of the propellant)



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) revision 02.12.2019 (GB) Version 7.6

Silikon-Öl-Spray

	Value	Temperature	at	Method	Remark
melting temperature	< -20 °C			DIN/ISO 3016	Details refer to the active agent (without consideration of the propellant)
Flash point	<0°C				information for solvent
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	ca. 300 °C				information concern solvent
Self ignition temperature	not determined				
Lower explosion limit	ca. 1 Vol-%				information concern solvent
Upper explosion limit	ca. 7,4 Vol-%				information concern solvent
Vapour pressure	ca. 250 hPa	20 °C			Details refer to the active agent (without consideration of the propellant)
Relative density	ca. 0,74 g/cm3	20 °C		pycnometer	information concerns to liquid phase
Vapour density	not determined				
Solubility in water					immiscible
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				



revision

02.12.2019 (GB) Version 7.6

Silikon-Öl-Spray

	Value	Temperature	at	Method	Remark
Viscosity	not determined				
Oxidising properties No information available.					
Explosive properties No information available.					
9.2. Other information No information available.					

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Formation of explosive gas/air mixtures.

Container under pressure. Protect from direct exposure to sunlight and temperatures exceeding 50°C.

10.5. Incompatible materials

Substances to avoid

Reactions with strong oxidising agents.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Additional information

Product is stable under normal storage conditions

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	5000 mg/kg	rat	OECD 401	Information concerns to main component.
LD50 acute dermal	3000 mg/kg	rat	OECD 402	
LC50 acute inhalation	172 mg/l (4 h)	rat	OECD	Details refer to the main component
Skin irritation	irritant	rabbit		
Eye irritation	strong irritant	rabbit eye		



revision 02.12.201

02.12.2019 (GB) Version 7.6

Silikon-Öl-Spray

 Value/Validation
 Species
 Method
 Remark

 Skin sensitization
 non-sensitizing
 Guinea pig

Toxicity test (Additional information)

There is no risk for a normal operation application

Experiences made from practice

Has a degreasing effect on the skin.

Frequent persistent contact with the skin may cause skin irritation.

Additional information

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

12.2. 1 0101010100	Elimination rate	Method of analysis	Method	Validation
Biological degradability				The main components are probably slightly degradable, but some components are
				persistent in the environment

valued

12.3. Bioaccumulative potential

Floats on water, is in liquid form, is adsorbed on Erdbodenpartikel partially and passes into the vapor phase. No groundwater contamination.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

14 06 03*

other solvents and solvent mixtures

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Dispose as specified by the public authorities.

Recommendations for packaging

Totally emptied packaging may be taken for recycling.



revision

02.12.2019 (GB) Version 7.6

Silikon-Öl-Spray

! SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	Druckgaspackung	Aerosols	Aerosols, flammable
14.3. Transport hazard class(es)	2	2	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available.

Land and inland navigation transport ADR/RID

tunnel restriction code D Classification code 5F No dangerous goods

Marine transport IMDG

According to ADR 5.2.1.8.1 products under 5 liters do not have to be drawn with the additional hazard "hazardous substance ." The main danger is due to the classification from the UN number.

Air transport ICAO/IATA-DGR

According to ADR 5.2.1.8.1 products under 5 liters do not have to be drawn with the additional hazard "hazardous substance ." The main danger is due to the classification from the UN number.

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Other regulations (EU)

Observe regulation 98/24/EC for employee health protection against the threat of chemical substances in the workplace.

Aerosol directive (75/324/EEC).

National regulations

Restriction of occupation

Observe employment restrictions for young people.

Water hazard class

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



revision 02.12.2019 (GB) Version 7.6

Silikon-Öl-Spray

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Further information

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 7.5

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.