


Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31



Printing date 29.03.2017

Revision: 29.03.2017

Trade name: Aerosol Coversall signalschwarz

	(Contd. of page 1)
• Hazard state	ements
H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
· Precautiona	ry statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P305+P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
• Additional in	nformation: Without adequate ventilation, explosive atmosphere/gas mix may be created.
· 2.3 Other ha	
	BT and vPvB assessment
· PBT: Not ap	
1	*

· **vPvB:** Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119471330-49-xxxx	• • • • • • • • • • • • • • • • • • • •	
CAS: 115-10-6	dimethyl ether	5-<10%
EINECS: 204-065-8	🚸 Flam. Gas 1, H220; 🔗 Press. Gas C, H280	
Reg.nr.: 01-2119472128-37-xxxx		
CAS: 74-98-6	propane	5-<10%
EINECS: 200-827-9	🚸 Flam. Gas 1, H220; 📀 Press. Gas C, H280	
Reg.nr.: 01-2119486944-21-xxxx		
CAS: 123-86-4	n-butyl acetate	5-<10%
EINECS: 204-658-1	🚸 Flam. Liq. 3, H226; 🔱 STOT SE 3, H336	
Reg.nr.: 01-2119485493-29-xxxx		
CAS: 106-97-8	butane (containing $\leq 0,1$ % butadiene (203-450-8))	5-<10%
EINECS: 203-448-7	🚸 Flam. Gas 1, H220; 🔗 Press. Gas C, H280	
Reg.nr.: 01-2119474691-32-xxxx		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	5-<10%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226	
Reg.nr.: 01-2119475791-29-xxxx	· -	
	(Con	td. on page 3)

Printing date 29.03.2017

Trade name: Aerosol Coversall signalschwarz

Revision: 29.03.2017

		ntd. of page
CAS: 9004-70-0	Nitrocellulose	2.5-<5%
	🚸 Flam. Sol. 1, H228	
CAS: 1330-20-7	xylene, mixture of isomers	2.5-<5%
EINECS: 215-535-7	 Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412 	
CAS: 75-28-5	isobutane (containing $\leq 0,1$ % butadiene (203-450-8))	2.5-<5%
EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	🚸 Flam. Gas 1, H220; 🔗 Press. Gas C, H280	
CAS: 64-17-5	ethanol	2.5-<5%
EINECS: 200-578-6	🛞 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319	
CAS: 100-41-4	ethylbenzene	1-<2.5%
EINECS: 202-849-4	🚯 Flam. Liq. 2, H225; 🚯 STOT RE 2, H373; Asp. Tox. 1,	ox. 1,
	H304; () Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2,	
	H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
CAS: 7397-62-8	butyl glycollate	<1%
EINECS: 230-991-7	🚯 Repr. 2, H361; 🛟 Eye Dam. 1, H318	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Cool container whit water
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

GB

(Contd. on page 5)

Revision: 29.03.2017 *Printing date 29.03.2017* Trade name: Aerosol Coversall signalschwarz (Contd. of page 3) · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. **SECTION 7: Handling and storage** · 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Take note of emission threshold. Use only in well ventilated areas. Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). · Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use. · 7.2 Conditions for safe storage, including any incompatibilities · Storage: • Requirements to be met by storerooms and receptacles: Store in a cool location. Observe official regulations on storing packagings with pressurised containers. · Information about storage in one common storage facility: Not required. · Further information about storage conditions: Protect from heat and direct sunlight. · 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection • Additional information about design of technical facilities: No further data; see item 7. · 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm *Carc* (*if more than* 0.1% *of buta-1.3-diene*)

106-97-8 butane (containing $\leq 0,1$ % butadiene (203-450-8))

115-10-6 dimethyl ether

123-86-4 n-butyl acetate

Printing date 29.03.2017

Revision: 29.03.2017

	(Contd. of page
108-6	5-6 2-methoxy-1-methylethyl acetate
	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk
1330-	20-7 xylene, mixture of isomers
	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV
64-17	-5 ethanol
	Long-term value: 1920 mg/m ³ , 1000 ppm
Ingre	dients with biological limit values:
-	20-7 xylene, mixture of isomers
	V 650 mmol/mol creatinine
2110	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
Wash Do no Avoid Avoid Respi When	diately remove all soiled and contaminated clothing hands before breaks and at the end of work. of inhale gases / fumes / aerosols. contact with the eyes. contact with the eyes and skin. ratory protection: workers are facing concentrations above the exposure limit they must use appropriate certific cators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply
Prote	ction of hands:
	(a) = m(a) = m
	love material has to be impermeable and resistant to the product/ the substance/ the preparation.
	tion of the glove material on consideration of the penetration times, rates of diffusion and th
	tion of the glove material on consideration of the penetration times, rates of diffusion and the dation
· Mater	tion of the glove material on consideration of the penetration times, rates of diffusion and th dation ial of gloves Nitrile rubber, NBR
• Mater • Penet	tion of the glove material on consideration of the penetration times, rates of diffusion and th dation rial of gloves Nitrile rubber, NBR ration time of glove material
• Mater • Penet Glove	tion of the glove material on consideration of the penetration times, rates of diffusion and the dation rial of gloves Nitrile rubber, NBR ration time of glove material as must be changed after every contamination.
• Mater • Penet Glove	tion of the glove material on consideration of the penetration times, rates of diffusion and the dation rial of gloves Nitrile rubber, NBR ration time of glove material is must be changed after every contamination. xact break trough time has to be found out by the manufacturer of the protective gloves and has to be
• Mater • Penet Glove The e. obser	tion of the glove material on consideration of the penetration times, rates of diffusion and the dation rial of gloves Nitrile rubber, NBR ration time of glove material is must be changed after every contamination. xact break trough time has to be found out by the manufacturer of the protective gloves and has to be
• Mater • Penet Glove The e. obser	tion of the glove material on consideration of the penetration times, rates of diffusion and the dation rial of gloves Nitrile rubber, NBR ration time of glove material is must be changed after every contamination. exact break trough time has to be found out by the manufacturer of the protective gloves and has to be ved. he permanent contact of a maximum of 15 minutes gloves made of the following materials a .
• Mater • Penet Glove The e. obser • For t suitab	tion of the glove material on consideration of the penetration times, rates of diffusion and the dation rial of gloves Nitrile rubber, NBR ration time of glove material is must be changed after every contamination. exact break trough time has to be found out by the manufacturer of the protective gloves and has to be ved. he permanent contact of a maximum of 15 minutes gloves made of the following materials a .
 Mater Penet Glove The e. obser For t. suitab butyl 	tion of the glove material on consideration of the penetration times, rates of diffusion and a dation rial of gloves Nitrile rubber, NBR ration time of glove material is must be changed after every contamination. exact break trough time has to be found out by the manufacturer of the protective gloves and has to wed. he permanent contact of a maximum of 15 minutes gloves made of the following materials of ble:

(Contd. on page 6)

GB

Printing date 29.03.2017

Revision: 29.03.2017

Trade name: Aerosol Coversall signalschwarz

(Contd. of page 5)

9.1 Information on basic physical and c	hemical properties
General Information	nemicui properties
Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: Not applicable, as aerosol.
Flash point:	<0 °C
	Without propellant gas.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	235 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	2.6 Vol %
Upper:	13.0 Vol %
Vapour pressure at 20 °C:	233 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	84.9 %
VOC (EU)	With propellant gas. Content given by weight. 84.92 %
Solids content:	15.1 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.

⁽Contd. on page 7)

Printing date 29.03.2017

Revision: 29.03.2017

Trade name: Aerosol Coversall signalschwarz

(Contd. of page 6)

- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: Possible in traces.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- \cdot Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

- Uncleaned packaging:
- *Recommendation:* Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA

UN1950

(Contd. on page 8)

GB -

Printing date 29.03.2017

Revision: 29.03.2017

de name: Aerosol Coversall signalschwar	7
	(Contd. of page
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS AEROSOLS Alammahla
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es) ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
	not classified
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	- not classified
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	 SW22 For AEROSOLS with a maximum capacity of 1 litr Category A. For AEROSOLS with a capacity above 1 litr Category B. For WASTE AEROSOLS: Category C, Clea of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litr Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capaci above 1 litre: Segregation as for the appropria subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Ann. Marpol and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL A L FO
Excepted quantities (EQ)	Code: E0
Transport catagory	Not permitted as Excepted Quantity 2
Transport category Tunnel restriction code	2 D
I WINDE FOSH WINDIE OUG	ν

Printing date 29.03.2017

Revision: 29.03.2017

Trade name: Aerosol Coversall signalschu	warz	
		(Contd. of page 8)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	50-100

- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

· Contact: Hr. Hamberger

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 10)

[·] Directive 2012/18/EU

GB

Printing date 29.03.2017

Revision: 29.03.2017

Trade name: Aerosol Coversall signalschwarz

	(Contd. of page 9)
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1: Flammable gases – Category 1	
Aerosol 1: Aerosols – Category 1	
Press. Gas C: Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Flam. Sol. 1: Flammable solids – Category 1	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
* Data compared to the previous version altered.	
	(