# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name: ESSENCE D'ASPIC

Product code: N135405.

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Registered company name: Max Sauer SAS.

Address: 2 rue Lamarck CS30204.22000.Saint Brieuc.France. Telephone: 0033(0)296682000. Fax: 0033(0)296770065.

mail@raphael.fr

# 1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

# **SECTION 2 : HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

# In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Aspiration hazard, Category 1 (Asp. Tox. 1, H304).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

#### 2.2. Label elements

# In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:









GHS07

GHS09

Signal Word: **DANGER** 

Product identifiers:

EC 242-060-2 (-)-PIN-2(10)-ENE (S-BETA-PINENE)

601-029-00-7 (R)-P-MENTHA-1,8-DIENE

EC 215-533-6 **PINENES** EC 201-291-9 PIN-2(3)-ENE

EC 209-578-0 P-MENTHA-1,4(8)-DIENE

EC 202-796-7 P-CYMENE

Hazard statements:

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Precautionary statements - Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash ... thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see ... on this label).

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.
P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use ... for extinction.

P391 Collect spillage.

 $Precautionary\ statements\ -\ Storage:$ 

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary statements - Disposal :

P501 Dispose of contents/container to ...

# 2.3. Other hazards

No data available.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.2. Mixtures

#### **Composition:**

Identification	(EC) 1272/2008	Note	%
CAS: 78-70-6	GHS07		25 <= x % < 50
EC: 201-134-4	Wng		
	Skin Irrit. 2, H315		
LINALOL			
CAS: 76-22-2	GHS07	[1]	10 <= x % < 25
EC: 200-945-0	Wng		
	Skin Irrit. 2, H315		
CAMPHRE	Eye Irrit. 2, H319		
	STOT SE 3, H335		

CAS: 18172-67-3	GHS09, GHS07, GHS08		2.5 <= x % < 10
EC: 242-060-2	Dgr		2.3 <= X /0 < 10
EC. 242-000-2	Asp. Tox. 1, H304		
(-)-PIN-2(10)-ENE (S-BETA-PINENE)	Skin Sens. 1, H317		
(-)-1 11(-2(10)-LIVE (B-BE171-1 11VEIVE)	Aquatic Acute 1, H400		
	M Acute = 1		
	Aquatic Chronic 1, H410		
	M Chronic = 1		
CAS: 98-55-5	GHS07		2.5 <= x % < 10
EC: 202-680-6	Wng		2.3 <= X /0 < 10
LC. 202-000-0	Skin Irrit. 2, H315		
P-MENTH-1-ENE-8-OL	Eye Irrit. 2, H319		
CAS: 79-92-5	GHS07, GHS09		2.5 <= x % < 10
EC: 201-234-8	Wng		2.3 <- X % < 10
EC. 201-234-6	Eye Irrit. 2, H319		
CAMPHENE	Aquatic Acute 1, H400		
CAMPHENE	M Acute = 1		
	Aquatic Chronic 1, H410		
	M Chronic = 1		
INDEX: 601 020 00 7	GHS02, GHS07, GHS09		2.5 <= x % < 10
INDEX: 601-029-00-7 CAS: 5989-27-5			$2.3 \le x \% < 10$
	Wng Flam. Liq. 3, H226		
EC: 227-813-5			
(D) D MENTHA 1.0 DIENE	Skin Irrit. 2, H315		
(R)-P-MENTHA-1,8-DIENE	Skin Sens. 1, H317		
	Aquatic Acute 1, H400		
	M Acute = 1		
	Aquatic Chronic 1, H410		
CAS: 1330-16-1	M Chronic = 1 GHS09, GHS07, GHS08		2.5 <= x % < 10
			$2.5 \le x \% < 10$
EC: 215-533-6	Dgr		
DIMENTED	Asp. Tox. 1, H304		
PINENES	Skin Sens. 1, H317		
	Aquatic Acute 1, H400		
	M Acute = 1		
	Aquatic Chronic 1, H410		
GAG 00.76.0	M Chronic = 1	F13	2.7
CAS: 80-56-8	GHS07, GHS09, GHS08	[1]	$2.5 \le x \% < 10$
EC: 201-291-9	Dgr		
DDI 4(4) ENE	Asp. Tox. 1, H304		
PIN-2(3)-ENE	Skin Irrit. 2, H315		
	Eye Irrit. 2, H319		
GAG 115 05 7	Aquatic Chronic 2, H411		1 2 2 2 2
CAS: 115-95-7	GHS09		$1 \le x \% < 2.5$
EC: 204-116-4	Aquatic Chronic 2, H411		
ACETATE I VNIAI VI E DIID			
ACETATE LYNALYLE PUR	CHEOO CHEOO		1 0/ 2.5
CAS: 586-62-9	GHS09, GHS08		$1 \le x \% < 2.5$
EC: 209-578-0	Dgr		
DIMENIUM 1 4(0) DIENE	Asp. Tox. 1, H304		
P-MENTHA-1,4(8)-DIENE	Aquatic Chronic 2, H411		1 . 0/ 2.7
CAS: 99-87-6	GHS07, GHS09, GHS08		$1 \le x \% < 2.5$
EC: 202-796-7	Dgr		
D 0717 071 17	Asp. Tox. 1, H304		
P-CYMENE	Skin Irrit. 2, H315		
	Aquatic Chronic 2, H411		

# Information on ingredients:

[1] Substance for which maximum workplace exposure limits are available.

# **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

#### 4.1. Description of first aid measures

# In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

### In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

#### In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

# 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

# **SECTION 5: FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

# 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

# Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

# Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

# 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

#### 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

# 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

## For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

# 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures. Use drums to dispose of collected waste in compliance with current regulations (see section 13).

# 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

#### 6.4. Reference to other sections

No data available.

# SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

# Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Never inhale this mixture.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

# Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

# Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

#### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

#### **Packaging**

Always keep in packaging made of an identical material to the original.

#### 7.3. Specific end use(s)

No data available.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

# Occupational exposure limits:

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:	
76-22-2	2 ppm	3 ppm	-	-	-	
80-56-8	20 ppm	-	-	-	-	
- France (INRS - ED98	4:2008):					
CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	$\ensuremath{TMP}\xspace\ensuremath{No}$ :
76-22-2	2	12	-	-	-	-
- UK / WEL (Workplace	e exposure limit	s, EH40/2005, 2	007):			
CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:	

# 8.2. Exposure controls

76-22-2

# Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):

3 ppm



2 ppm





Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

## - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- PVA (Polyvinyl alcohol)

Recommended properties:

- Impervious gloves in accordance with standard EN374

### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

#### **General information:**

Physical state: Viscous liquid.

Important health, safety and environmental information

pH: Not stated.

Neutral.

Boiling point/boiling range :  $> 35^{\circ}$ C Flash Point :  $20.00^{\circ}$ C.

Vapour pressure (50°C): Below 110 kPa (1.10 bar).

Density: >1

Water solubility: Insoluble.

 $\begin{tabular}{lll} Viscosity: & v < 7 mm2/s (40 °C) \\ Melting point/melting range: & Not specified. \\ Self-ignition temperature: & Not specified. \\ Decomposition point/decomposition range: & Not specified. \\ \end{tabular}$ 

## 9.2. Other information

No data available.

# **SECTION 10: STABILITY AND REACTIVITY**

## 10.1. Reactivity

No data available.

# 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

# 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

#### Avoid

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

# SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

May cause an allergic reaction by skin contact.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

#### 11.1.1. Substances

# Acute toxicity:

CAMPHRE (CAS: 76-22-2)

Oral route: LD50 > 5000 mg/kg

Species: Rat

Inhalation route (Vapours) : LC50 = 0.5 mg/l

Species: Rat

# 11.1.2. Mixture

No toxicological data available for the mixture.

# Aspiration hazard:

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

# **SECTION 12 : ECOLOGICAL INFORMATION**

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

# 12.1. Toxicity

# 12.1.1. Substances

CAMPHRE (CAS: 76-22-2)

Fish toxicity: Duration of exposure: 96 h

LC50 = 35 mg/l Species : Danio rerio

## **12.1.2.** Mixtures

No aquatic toxicity data available for the mixture.

# 12.2. Persistence and degradability

No data available.

# 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

No data available.

#### 12.6. Other adverse effects

No data available.

#### SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

## 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

# **SECTION 14: TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

#### 14.1. UN number

1263

# 14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

# 14.3. Transport hazard class(es)

- Classification:



3

# 14.4. Packing group

III

### 14.5. Environmental hazards

- Environmentally hazardous material :



# 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	-	5 L	163 367 650	E1	3	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	3	-	III	5 L	F-E,S-E	163 223 367 955	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ

	3	-	III	355	60 L	366	220 L	A3 A72	E1
								A192	
ĺ	3	-	III	Y344	10 L	-	-	A3 A72	E1
								A192	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

#### **SECTION 15: REGULATORY INFORMATION**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

 $Packaging \ to \ be \ fitted \ with \ child-resistant \ fastenings \ (see \ EC \ Regulation \ No. \ 1272/2008, Annex \ II, \ Part \ 3).$ 

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

#### - Particular provisions :

No data available.

# - Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704):

NFPA 704, Labelling: Health=2 Inflammability=3 Instability/Reactivity=1 Specific Risk=none



#### 15.2. Chemical safety assessment

No data available.

## **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

# Wording of the phrases mentioned in section 3:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

# **Abbreviations:**

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

GHS02: Flame

GHS07 : Exclamation mark GHS08 : Health hazard GHS09 : Environment