

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.09.2019 Version number 1.2 Revision: 17.09.2019

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: KREUL Magic Marble Marbling paint 20 ml
- · Article number: 73201 73237, 73600, 73610 73614, 73703, 732091
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Paint

For artists and hobby user.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

C. KREUL GmbH & Co. KG

Carl-Kreul-Straße 2

D-91352 HALLERNDORF

DEUTSCHLAND

Tel. + 49 (0)9545 / 925 - 0

Fax + 49 (0)9545 / 925 - 511

E-Mail: info@c-kreul.de

Further information obtainable from:

Product Safety Department:

Treiber, b.treiber@c-kreul.de

· 1.4 Emergency telephone number: +44 (0)171 635 91 91

2 Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02

GHS07

- Signal word Warning
- Hazard-determining components of labelling:

1-methoxy-2-propanol

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

2-methoxy-1-methylethyl acetate

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use for extinction: CO2, sand, extinguishing powder.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.09.2019 Version number 1.2 Revision: 17.09.2019

(Contd. of page 1)

· Additional information:

EUH208 Contains cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

· 2.3 Other hazards

Vapours may form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/ electrical equipment). Take precautionary measures against static discharges.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	25-<50%
CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	10-<20%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate → Flam. Liq. 3, H226; → STOT SE 3, H336	5-<10%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39-XXXX	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics Asp. Tox. 1, H304	5–<10%

· Additional information:

Benzene (EINECS 200-753-7) < 0.1%. (Note P Annex VI to Directive (EC) No 1272/2008)

For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

Seek immediate medical advice.

· After skin contact:

Wash with water and acidic soap.

If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Administer medicinal carbon.

A person vomiting while laying on their back should be turned onto their side.

Seek immediate medical advice.

- $\hbox{\bf \cdot 4.2 Most important symptoms and effects, both acute and delayed $\hbox{No further relevant information available}. } \\$
- 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

5 Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1.2 Revision: 17.09.2019 Printing date 17.09.2019

(Contd. of page 2)

Use respiratory protective device against the effects of fumes/dust/aerosol.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Mount respiratory protective device.

6.2 Environmental precautions:

Keep contaminated washing water and dispose of appropriately.

In case of seepage into the ground inform responsible authorities.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Take note of emission threshold.

Prevent formation of aerosols.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

Further information about storage conditions:

Keep container tightly sealed.

107-98-2 1-methoxy-2-propanol

Oral

Dermal

Store receptacle in a well ventilated area.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

long-term exposure-systemic effects 33 mg/kg (general population)

long-term exposure-systemic effects 183 mg/kg bw/d (general population)

	ol parameters	ical facilities: No further data; see item 7.
· Ingredien	ts with limit values that require mor	nitoring at the workplace:
107-98-2 1	-methoxy-2-propanol	
	rt-term value: 560 mg/m³, 150 ppm g-term value: 375 mg/m³, 100 ppm	
108-65-6 2	2-methoxy-1-methylethyl acetate	
WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk		
DNELs		
64742-48-	9 Hydrocarbons, C9-C11, n-alkanes	, iso-alkanes, cyclenes, <2% aromatics
Oral	long-term exposure-systemic effects	300 mg/kg (general population)
Dermal	long-term exposure-systemic effects	300 mg/kg bw/d (general population)
		300 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	900 mg/m³ (general population)
		1,500 mg/m³ (worker)
108-65-6 2	2-methoxy-1-methylethyl acetate	
Oral	long-term exposure-systemic effects	1.67 mg/kg (general population)
Dermal	long-term exposure-systemic effects	54.8 mg/kg bw/d (general population)
		153.5 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	33 mg/m³ (general population)
		275 mg/m³ (worker)

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.09.2019 Version number 1.2 Revision: 17.09.2019

		(Contd. of page
	7	78 mg/kg bw/d (worker)
Inhalative long-term exposure	systemic effects 4	43.9 mg/m³ (general population)
	3	369 mg/m³ (worker)
· PNECs		
107-98-2 1-methoxy-2-propar	ol	
water	100 mg/l	
freshwater	10 mg/l	
marine water	1 mg/l	
sewage treatment plant (STP)	100 mg/l	
freshwater sediment	52.3 mg/kg	
marine sediment	5.2 mg/kg	
108-65-6 2-methoxy-1-methyl	ethyl acetate	
water	635 mg/l	
freshwater	0.635 mg/l	
marine water	0.0635 mg/l	
sewage treatment plant (STP) 100 mg/l		
freshwater sediment 3.29 mg/kg		
marine sediment	0.329 mg/kg	
soil 0.29 mg/kg		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not eat, drink, smoke or sniff while working.

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device when high concentrations are present.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.38 mm

Value for the permeation: Level ≤ 4 h

As protection from splashes gloves made of the following materials are suitable:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.3 mm Value for the permeation: Level ≤ 10 - 30 min

Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information
- Appearance:

Form: Fluid

Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.

pH-value: Not determined.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.09.2019 Version number 1.2 Revision: 17.09.2019

	(Contd. of page
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : Undetermined.
Flash point:	25 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures a possible.
Explosion limits: Lower: Upper:	0.6 Vol % 13.8 Vol %
Vapour pressure:	Not determined.
Density at 20 °C: Relative density Vapour density Evaporation rate	0.9–1.1 g/cm³ Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic at 40 °C:	Not determined. >20.5 mm²/s
Solvent content: Organic solvents: VOC (EC) 9.2 Other information	65-80 % 67.42–77.69 % No further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Keep away from oxidizing agents, strong alkaline and acidic materials.
- 10.6 Hazardous decomposition products:

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
107-98-2	1-methox	y-2-propanol	
Oral	LD50	5,660 mg/kg (rat)	
Dermal	LD50	13,000 mg/kg (rabbit)	
64742-48	64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>3,000 mg/kg (rab)	
108-65-6	2-methox	y-1-methylethyl acetate	
Oral	LD50	8,532 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rab)	
Inhalative	LC50/4h	35.7 mg/m³ (rat)	

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- $\cdot \textbf{Carcinogenicity} \ \text{Based on available data, the classification criteria are not met.} \\$

(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1.2 Printing date 17.09.2019 Revision: 17.09.2019

(Contd. of page 5)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

· 12.1 Toxicity

		y		
ſ	· Aquatic toxicity:			
Ī	Hydrocark	oons, C10-C13, n-alkanes, iso-alkanes, cyclenes, <2% aromatics		
Ī	LC50/48h	>1,000 mg/l (oncorhynchus mykiss)		
	EC50/48h	>1,000 mg/l (daphnia magna)		
	EC50/72h	>1,000 mg/l (pseudokirchneriella subcapitata)		
ĺ	108-65-6 2	-methoxy-1-methylethyl acetate		
ĺ	LC50/96h	134 mg/l (oncorhynchus mykiss)		
	EC50/48h	>500 mg/l (daphnia magna)		

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- **General notes:**

Magic Marble Red, Orange, Sun Yellow: Water hazard class 3 (self-classification): highly hazardous to water Magic Marble Black, Silver, Gold, Copper, Volcanic Gray matt, Metallic Red, Metallic Violet, Metallic Blue, Metallic Green, Neon Yellow, Neon Orange, Neon Pink: Water hazard class 2 (self-classification): significantly hazardous to water

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Danger to drinking water if even extremely small quantities leak into the ground.

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
15 01 10*	packaging containing residues of or contaminated by hazardous substances	
15 01 07	glass packaging	
HP 3	Flammable	
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· 14.1 UN-Number
ADD IMPC IATA

UN1263 ADR, IMDG, IATA

· 14.2 UN proper shipping name

ADR **1263 PAINT** · IMDG, IATA **PAINT**

- · 14.3 Transport hazard class(es)
- · ADR. IMDG. IATA



· Class 3 Flammable liquids. 3

· Label

· 14.4 Packing group

 ADR, IMDG, IATA Ш

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1.2 Revision: 17.09.2019 Printing date 17.09.2019

	(Contd. of page
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· 14.7 Transport in bulk according to Annex	(II of Marpol
and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product Safety Department
- · Contact: B. Treiber, b.treiber@c-kreul.de
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

PBT: Persistent, bloaccumulative and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

·* Data compared to the previous version altered.