Article Print c Versic	date 12.0	008XXX)1.2017	GOLDFINGER Revision date 12.01 Issue date 12.01.20		EN Page 1 / 7
1.	Identification of	of the substa	ance/mixture and c	of the company/und	ertaking
1.1.	Product identifi Article No. (manu Identification of t	ufacturer/suppl		145008XXX GOLDFINGER SOVEREIGN GOLD, ANTIQUE GOLD, CO	
1.2.	Relevant identif Relevant identif Artists supply an Coatings and pa	ïed uses: d hobby prepa	rations	ture and uses advised	l against
1.3.			safety data sheet		
	Supplier (manuf Daler-Rowney Lt Peacock Lane Bracknell, RG12 ENGLAND Dept. responsib	d 8SS	rter/downstream use	er/distributor): Telephone: +44 (0) 13 Telefax: +44 (0) 1344	
	E-mail			Philip.Gray@daler-rov	vney.com
1.4.	Emergency tele Emergency telep	-	r	+44 (0) 1344 461000	
2.	Hazards identi	fication			
2.2.				Flammable liquid and vapour. Harmful to aquatic life with long lasting effects.	
	Hazard stateme				
	H226 H412		ble liquid and vapour. to aquatic life with lor		
	Precautionary s P101 P102 P103 P210 P233 P273 P280 P303 + P361 + F P370 + P378 P403 + P235 P501 contains: Supplemental H	If medica Keep ou Read lat Keep aw Keep co Avoid re Wear pr 2353 IF ON St water/sh In case o Store in Dispose	t of reach of children. bel before use. vay from heat, hot sum ntainer tightly closed. lease to the environm otective gloves/protec KIN (or hair): Remove ower. of fire: Use foam to ex a well-ventilated place of contents/container	faces, sparks, open fla lent. ctive clothing/eye prote c/Take off immediately ctinguish.	mes and other ignition sources. No smoking. ction/face protection. all contaminated clothing. Rinse skin with
	EUH066			se skin dryness or cracl	king.

Article Print o Versio	date	145008XXX 12.01.2017 1.2	GOLDFINGER Revision date 12.01.2017 Issue date 12.01.2017	EN Page 2 / 7				
	EUH208	Conta	ns isobutyl methacrylate.May produce a	an allergic reaction.				
2.3.	Other haza	rds						
		uch as cleaning isly self-ignite sor	rags, paper wipes and protective clone hours later.	othing, which are contaminated	I with the product may			
3.	Composit	ion / Informatio	on on ingredients					
3.2.	Mixtures							
	Product de	escription / chem	ical characterization					
	Description							
	Hazardous	Description oil paint Hazardous ingredients						
	Classificat	ion according to	Regulation (EC) No. 1272/2008 [CLP]					
	EC No.	REAC	H No.					
	CAS No.		ical name		Wt %			
	INDEX No.		fication:		Remark			
	918-167-1	• · = ·	19472146-39					
	64741-65-7		carbons, C11-C12, Isoalkanes, <2% Arc Liq. 3 H226 / Asp. Tox. 1 H304 / Aqu		12,5 - 20			
	265-192-2							
	64742-89-8	Solver	nt naphtha (petroleum), light aliph.		2,5 - 5			
	649-267-00-0 Flam. Liq. 2 H225 / Skin Irrit. 2 H315 / Asp. Tox. 1 H304 / STOT H336 / Aquatic Chronic 2 H411		Asp. Tox. 1 H304 / STOT SE 3					
	202-613-0	01-21	19488331-38-xxxx					
	97-86-9	isobut	yl methacrylate		< 0,5			
	607-113-00		Liq. 3 H226 / Eye Irrit. 2 H319 / S / Skin Sens. 1 H317 / Aquatic Acute 1					
	Additional	information						

Additional information

Full text of classification: see section 16

4. First-aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons: strong water jet

Article No.:	145008XXX	GOLDFINGER		
Print date	12.01.2017	Revision date 12.01.2017	EN	
Version	1.2	Issue date 12.01.2017	Page 3 / 7	

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage. Vapours form explosive mixtures with air.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Cool closed containers that are near the source of the fire.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations. Vapours form explosive mixtures with air.

6.3. Methods and material for containment and cleaning up Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13).

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

7. Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

8. Exposure controls / Personal protection

8.1. Control parameters

Occupational exposure limit values:

n.a.

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and

Article No.:	145008XXX	GOLDFINGER		
Print date	12.01.2017	Revision date 12.01.2017	EN	
Version	1.2	Issue date 12.01.2017	Page 4 / 7	

solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	liquid
Physical state	liquid
Colour	refer to label
Odour	characteristic

Safety relevant basis data		Unit	Method	Remark
Flash point:	< 60	°C	DIN 53213	
Ignition temperature in °C:	355	°C		
Lower explosion limit	0,6	Vol-%		
Upper explosion limit	6,0	Vol-%		
Vapour pressure at 20 °C:	0,01	mbar		
Density at 20 °C:	1,00	g/cm³		
Water solubility (g/L)	insoluble			
pH at 20 °C:	-			
Viscosity at 20 °C	< 60	mPa·s		
Solvent separation test (%)	< 3	%		
boiling point in °C at 101,3 kPa	100	°C		
Other information:				

10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. Vapours form explosive mixtures with air.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide,

Article No.:	145008XXX	GOLDFINGER		
Print date	12.01.2017	Revision date 12.01.2017	EN	
Version	1.2	Issue date 12.01.2017	Page 5 / 7	

smoke, nitrogen oxides.

11. Toxicological information

Classification according to Regulation (EC) No. 1272/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Hydrocarbons, C11-C12, Isoalkanes, <2% Aromatics oral, LD50, Rat: > 5000 mg/kg Method: OECD 401 dermal, LD50, Rabbit: > 5000 mg/kg

Solvent naphtha (petroleum), light aliph.

inhalative (vapours), LC50, Rat: > 5,61 mg/L (4 h)

skin corrosion/irritation; Serious eye damage/eye irritation

Hydrocarbons, C11-C12, Isoalkanes, <2% Aromatics

Skin (4 h)

Causes mild skin irritation. Eyes: evaluation Not an irritant.

Respiratory or skin sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

12. Ecological information

overall evaluation

Classification according to Regulation (EC) No. 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

Solvent naphtha (petroleum), light aliph.

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 8,2 mg/L (96 h) Daphnia toxicity, EC50, Daphnia magna (Big water flea): 4,8 mg/L (48 h) Algae toxicity, ErC50, Selenastrum capricornutum: 3,1 mg/L (72 h) Method: OECD 201

Long-term Ecotoxicity

Solvent naphtha (petroleum), light aliph. Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 2,6 mg/L (21 d)

12.2. Persistence and degradability

Toxicological data are not available.

Article No.: Print date Version	12.01.2017	GOLDFINGER Revision date 12.01.2017 Issue date 12.01.2017	EN Page 6 / 7		
	accumulative potential cological data are not availal	ble.			
	Mobility in soil Toxicological data are not available.				
12.5. Res	ults of PBT assessment				
The	substances in the mixture do	o not meet the PBT/vPvB criteria	according to REACH, annex XIII.		
12.6. Oth	er adverse effects				
13. Dis	posal considerations				
13.1. Was	ste treatment methods				
	oropriate disposal / Product				
	ommendation				
		e water or drains. This material a 008/98/EC, covering waste and d	and its container must be disposed of in a safe way. Waste angerous waste.		
-	-	waste designations in accorda	-		
080		nt and varnish other than those m			
	kaging				
	ommendation	who recycled Vessels not prope	rly emptied are special waste. Send to a collecting point for		
	d paints.	y be recycled. Vessels not prope	iny emplied are special waste. Send to a collecting point for		
	nsport information				
14.1. UN r	•				
14.1. UN1	lullibel	UN 1263			
14.2. UN p	proper shipping name				
Lan	d transport (ADR/RID):	Paint			
	transport (IMDG):	PAINT			
	ransport (ICAO-TI / IATA-DG	R): Paint			
14.3. 11 a 11	sport hazard class(es)	3			
14.4. Pac	king group				
		111			
14.5. Env	ironmental hazards				
Lan	d transport (ADR/RID)	n.a.			
Mar	ine pollutant	n.a.			
14.6. Spe	cial precautions for user				
		ht and safe containers. Make sur	e that persons transporting the product know what to do in		
	case of an accident or leakage. Advices on safe handling: see parts 6 - 8				
	0 1	1115 0 - 0			
	litional information				
	d transport (ADR/RID)	5.5			
tunn	el restriction code	D/E			
	transport (IMDG)				
	S-No.	F-E, S-E			
	nsport in bulk according to applicable	Annex II of MARPOL and the II	3C Code		
SEC	CTION 15: Regulatory inf	ormation			
15.1. Safe	ety, health and environmen	tal regulations/legislation spec	ific for the substance or mixture		
	legislation				
	-	13/EC about limitation of emiss	sions of volatile organic compounds (VOC-guideline).		
	C-value (in g/L) ISO 11890-2:		2		

Article No.: Print date Version		145008XXX 12.01.2017 1.2	GOLDFINGER Revision date 12.01.2017 Issue date 12.01.2017		EN Page 7 / 7	
	VOC-value (i National reg	in g/L) ASTM D 23 julations	69:	142		
	Observe emp				35/EEC) for expectant or nursing mothers. protection guideline' (94/33/EC).	
	Other regula	ations, restriction	and prohibition regulations			
15.2.	Chemical Sa	afety Assessmen		al safety assess	sment has been carried out:	
	EC No. CAS No.	Chemic	al name		REACH No.	
			rbons, C11-C12, Isoalkanes, <2% Aromatics		01-2119472146-39	
16.	Other infor	mation				
	Full text of o	classification in s	section 3:			
	Flam. Liq. 3		flammable liquids		lammable liquid and vapour.	
	Asp. Tox. 1 /		Aspiration hazard		lay be fatal if swallowed and enters airways.	
	Aquatic Chro	onic 4 / H413	Hazardous to the aquatic enviro		lay cause long lasting harmful effects to quatic life.	
	Flam. Liq. 2	/ H225	flammable liquids	H	lighly flammable liquid and vapour.	
	Skin Irrit. 2 /	H315	skin corrosion/irritation	C	auses skin irritation.	
	STOT SE 3 /	H336	Specific target organ toxicity (si exposure)	ingle M	lay cause drowsiness or dizziness.	
	Aquatic Chro	onic 2 / H411	Hazardous to the aquatic enviro	onment T	oxic to aquatic life with long lasting effects.	
	Eye Irrit. 2 / I		Serious eye damage/eye irritati	ion C	auses serious eye irritation.	
	STOT SE 3 /		Specific target organ toxicity (si exposure)		lay cause respiratory irritation.	
	Skin Sens. 1	/ H317	respiratory or skin sensitisation	N	lay cause an allergic skin reaction.	
	Aquatic Acut	e 1 / H400	Hazardous to the aquatic enviro		ery toxic to aquatic life.	
	Abbroviatio	ne and acronyme				

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Additional information

Classification according to Regulation (EC) No. 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.