# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name: VERNIS EXTRA FINA TABLEAUX

Product code: N135101. 103. 105...

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Registered company name: Max Sauer SAS.

Address: 2 rue Lamarck CS30204.22000.Saint Brieuc.France. Telephone: 0033(0)296682000. Fax: 0033(0)296770065.

mail@raphael.fr

# 1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

# **SECTION 2 : HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

# In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).

Acute dermal toxicity, Category 4 (Acute Tox. 4, H312).

Acute inhalation toxicity, Category 4 (Acute Tox. 4, H332).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

# 2.2. Label elements

# In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:







GHS02

GHS07

GHS09

)9

Signal Word : DANGER

Product identifiers:

ESSENCE DE TÉRÉBENTHINE

603-001-00-X METHANOL

Hazard statements:

H225 Highly flammable liquid and vapour.

H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P103 Read label before use.

Precautionary statements - Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash ... thoroughly after handling.

P270 Do no eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see ... on this label).
P322 Specific measures (see ... on this label).

P330 Rinse mouth.

P332 + P313If skin irritation occurs: Get medical advice/attention.P333 + P313If skin irritation or rash occurs: Get medical advice/attention.P337 + P313If eye irritation persists: Get medical advice/attention.P362Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse. P370 + P378 In case of fire: Use ... for extinction.

P391 Collect spillage.

Precautionary statements - Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary statements - Disposal:

P501 Dispose of contents/container to ...

# 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

#### **Composition:**

Identification	(EC) 1272/2008	Note	%
ESSENCE DE TÉRÉBENTHINE	GHS07, GHS09, GHS08		50 <= x % < 100
	Dgr		
	Acute Tox. 4, H302		
	Asp. Tox. 1, H304		
	Acute Tox. 4, H312		
	Skin Irrit. 2, H315		
	Skin Sens. 1, H317		
	Eye Irrit. 2, H319		
	Acute Tox. 4, H332		
	Aquatic Chronic 2, H411		
INDEX: 603-117-00-0	GHS02, GHS07	[1]	2.5 <= x % < 10
CAS: 67-63-0	Dgr		
EC: 200-661-7	Flam. Liq. 2, H225		
	Eye Irrit. 2, H319		
PROPAN-2-OL	STOT SE 3, H336		
INDEX: 603-001-00-X	GHS02, GHS06, GHS08	[1]	$0 \le x \% < 1$
CAS: 67-56-1	Dgr		
EC: 200-659-6	Flam. Liq. 2, H225		
	Acute Tox. 3, H331		
METHANOL	Acute Tox. 3, H311		
	Acute Tox. 3, H301		
	STOT SE 1, H370		

#### **Information on ingredients:**

[1] Substance for which maximum workplace exposure limits are available.

#### **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

#### 4.1. Description of first aid measures

# In the event of exposure by inhalation:

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Do not proceed with mouth-to-mouth or mouth-to-nose resuscitation. Use the appropriate equipment.

# In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

# In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

## In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

#### SECTION 5: FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

#### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

# Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

#### Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

#### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

## 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

# 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

# For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

# For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

# 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures. Use drums to dispose of collected waste in compliance with current regulations (see section 13).

# 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

#### 6.4. Reference to other sections

No data available.

#### SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

#### Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

# Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

## Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

# 7.2. Conditions for safe storage, including any incompatibilities

No data available.

### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

#### **Packaging**

Always keep in packaging made of an identical material to the original.

#### 7.3. Specific end use(s)

No data available.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1. Control parameters

#### Occupational exposure limits:

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

CAS TWA: STEL: Ceiling: Definition: Criteria: 67-63-0 200 ppm 400 ppm - - - - - - 67-56-1 200 ppm 250 ppm - - - - -

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS VME: VME: Excess Notes
67-63-0 200 ml/m3 500 mg/m3 2(II) DFG, Y
67-56-1 200 ml/m3 270 mg/m3 4(II) DFG, EU, H, Y

- France (INRS - ED984:2008):

CAS VME-ppm: VME-mg/m3: VLE-ppm: VLE-mg/m3: Notes: TMP No: 67-63-0 400 980 84 67-56-1 200 260 1000 1300 (12)84 - UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

#### 8.2. Exposure controls

# Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):









Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

## - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- PVA (Polyvinyl alcohol)

#### Recommended properties:

- Impervious gloves in accordance with standard EN374

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

# - Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

- A1 (Brown)

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

#### **General information:**

Boiling point/boiling range:

Physical state: Viscous liquid.

Important health, safety and environmental information

pH: Not stated.

Neutral. > 35°C

Flash Point : 12.00 °C.
Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density: >1

Water solubility: Insoluble.

Melting point/melting range: Not specified.

Self-ignition temperature: Not specified.

Decomposition point/decomposition range: Not specified.

#### 9.2. Other information

No data available.

# SECTION 10: STABILITY AND REACTIVITY

# 10.1. Reactivity

No data available.

# 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

# 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

#### Avoid:

- accumulation of electrostatic charges.
- heating
- heat

- flames and hot surfaces

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful if swallowed.

Harmful in contact with skin.

Harmful by inhalation.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

May cause an allergic reaction by skin contact.

# 11.1.1. Substances

No toxicological data available for the substances.

## 11.1.2. Mixture

No toxicological data available for the mixture.

# SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

# 12.1. Toxicity

# **12.1.2.** Mixtures

No aquatic toxicity data available for the mixture.

# 12.2. Persistence and degradability

No data available.

# 12.3. Bioaccumulative potential

No data available.

# 12.4. Mobility in soil

No data available.

# 12.5. Results of PBT and vPvB assessment

No data available.

### 12.6. Other adverse effects

No data available.

# SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

# 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

## Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

#### **SECTION 14: TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

#### 14.1. UN number

1263

# 14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

#### 14.3. Transport hazard class(es)

- Classification:



3

# 14.4. Packing group

II

# 14.5. Environmental hazards

- Environmentally hazardous material:



# 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	5 L	163 367 640D 650	E2	2	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	3	-	II	5 L	F-E,S-E	163 367	E2

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	II	353	5 L	364	60 L	A3 A72	E2
								A192	
	3	-	II	Y341	1 L	-	-	A3 A72	E2
								A192	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

# **SECTION 15: REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### - Classification and labelling information included in section 2:

The following regulations have been used:

- Regulation EC 1272/2008 modified by regulation EC 618/2012
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.

#### - Container information:

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

# - Particular provisions :

No data available.

# - Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704):

NFPA 704, Labelling: Health=2 Inflammability=3 Instability/Reactivity=1 Specific Risk=none



#### 15.2. Chemical safety assessment

No data available.

#### **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

# Wording of the phrases mentioned in section 3:

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs .
H411	Toxic to aquatic life with long lasting effects.

#### **Abbreviations:**

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

GHS02: Flame

GHS07 : Exclamation mark GHS09 : Environment