

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No.
Version 6 (23.01.18)

Issue date: 23.01.18
Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name 50 008 - Dammar varnish, glossy

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use
Products for creation of art.

Uses advised against

1.3 Details of the supplier of the safety data sheet

H. Schmincke & Co. GmbH & Co. KG
Otto-Hahn-Str. 2
D - 40699 Erkrath
Tel. +49 (0) 211-2509-0
Fax. +49 (0) 211-2509-497
info@schmincke.de
www.schmincke.de

Dept. responsible for information
Schmincke-lab:
mo-th 8.00-16.30, fr 8.00-13.30
Tel. +49 (0) 211-2509-474
labor@schmincke.de

1.4 Emergency telephone number

Emergency
Information
Phone #

Emergencycall Berlin
(24h - counseling in german and english)
+49 (0) 30-30686700

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aquatic Chronic 2; H411 Toxic to aquatic life with long lasting effects.
Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.
Flam. Liq. 3; H226 Flammable liquid and vapour.
STOT SE 3; H335 May cause respiratory irritation.
STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling (CLP)



Signal word Danger

Hazard statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Safety precautions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

| | | | |
|-------------|----------------|-------------|----------|
| Article No. | | Issue date: | 23.01.18 |
| Version | 6 (23.01.18) | Page | 2 / 9 |

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take action to prevent static discharges.
P260 Do not breathe vapours.
P273 Avoid release to the environment.
P280 P273 Avoid release to the environment.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/..
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower.
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

2.3 Other hazards

Repeated exposure may cause skin dryness or cracking. (EUH066)

SECTION 3: Composition / information on ingredients

3.1 Substances

Chemical characterisation

White spirit
Dammar resin

CAS-Number
EINECS / ELINCS / NLP
EU index number
Customs tariff number
REACH registration No.
RTECS-no.
Hazchem-Code
CI-Number

3.2 Mixtures

| Substance 1 |
|-------------|
|-------------|

Solvent naphtha (petroleum), light, aromatic: 60 - 70 %
CAS-Number: 64742-95-6
REACH registration No.: 01-2119455851-35
Classification according to EC regulation 1272/2008 (CLP):
Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE 3; H336 / EUH066

Additional information

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If you feel unwell, seek medical advice (show the label where possible).

In case of inhalation

Provide fresh air. Seek medical attention if problems persist.

In case of skin contact

Remove residues with soap and water. In case of skin irritation, consult a physician.

After eye contact

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 10 - 15 minutes. Seek medical attention if irritation persists.

After swallowing

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

| | | | |
|-------------|----------------|-------------|----------|
| Article No. | | Issue date: | 23.01.18 |
| Version | 6 (23.01.18) | Page | 3 / 9 |

Rinse mouth with water. Seek medical treatment in case of troubles.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration!

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons

strong water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters

Use appropriate respiratory protection.

Additional information

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes, and clothing.

6.2 environmental precautions

Discharge into the environment must be avoided.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Collect spilled material using paper towels and dispose.

Additional information

6.4 Reference to other sections

Dispose of waste according to applicable legislation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Precautions against fire and explosion

No special measures are required.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers

Hints on joint storage

Storage class

Further details

Protect from frost and exposure to sun.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

64742-95-6 solvent naphtha (petroleum), light, aromatic

| | | | | |
|-----|-----|---------|-------------------|----------|
| DEU | WEL | 100,000 | mg/m ³ | TRGS 900 |
|-----|-----|---------|-------------------|----------|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

| | | | |
|-------------|----------------|-------------|----------|
| Article No. | | Issue date: | 23.01.18 |
| Version | 6 (23.01.18) | Page | 4 / 9 |

8.2 Exposure controls

Occupational exposure controls

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.
Respiratory protection must be worn whenever the WEL levels have been exceeded.
Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

Hand protection

Qualified materials: Nitrile rubber
Layer thickness > 0,35 mm
Breakthrough time > 480 min
Ultranitril 492 - MAPA GmbH, Industriestraße 21- 25, D-27404 Zeven, Internet: www.mapa-pro.de
All information was derived in accordance with EU directive 89/686/EEC and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves. This information is based on our current state of knowledge and describes the security standards applicable to our product for the purpose provided.

Eye protection

Goggles

Body protection

Wear suitable protective clothing. Wash contaminated clothing prior to re-use.

General protection and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands thoroughly after handling.

SECTION 9: Physical and chemical properties

9.1 information on basic physical and chemical properties

| | |
|--------|------------------|
| Form | liquid |
| Colour | yellowish, clear |
| Odour | weak aromatic |

| | min | max |
|-----------------------------------------|-------|-------|
| Initial boiling point and boiling range | | |
| Melting point/freezing point | | |
| Flash point/flash point range | 34 °C | 34 °C |
| Flammability | | |
| Ignition temperature | | |
| Auto-ignition temperature | | |
| Explosion limits | | |
| Refraction index | | |

Partition coefficient: n-octanol/water

Danger of explosion

Vapour pressure

Density 0,87 g/ml 20 °C

PH value

Viscosity dynamic of

Viscosity dynamic up to

Viscosity kinematic of 8 mm²/s 40 °C

Viscosity kinematic up to 9 mm²/s 40 °C

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

Product is stable under normal storage conditions.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No.
Version 6 (23.01.18)

Issue date: 23.01.18
Page 5 / 9

10.2 Chemical stability

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Protect from frost and exposure to sun.

10.5 Incompatible materials

strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous vapours may form during fires.

64742-95-6 solvent naphtha (petroleum), light, aromatic

| | | | | | | |
|--------|------|-----|---|----------|-------|---|
| oral | LD50 | Rat | > | 2000,000 | mg/kg | - |
| dermal | LD50 | Rat | > | 2000,000 | mg/kg | - |

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

In case of inhalation

No data available

After swallowing

No data available

In case of skin contact

No data available

After eye contact

No data available

Practical experience

General remarks

Toxicological tests

64742-95-6 solvent naphtha (petroleum), light, aromatic

| | | | | | |
|------|-------|---|--------|------|---|
| LC50 | fish | > | 10,000 | mg/l | - |
| LC50 | Algae | > | 10,000 | mg/l | - |

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

No data available

Water Hazard Class

non hazardous to water

WGK catalog number

General information

12.2 Persistence and degradability

Further details

Product is partially biodegradable.

Oxygen demand

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)

Partition coefficient: n-octanol/water

12.4 Mobility in soil

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

| | | | |
|-------------|----------------|-------------|----------|
| Article No. | | Issue date: | 23.01.18 |
| Version | 6 (23.01.18) | Page | 6 / 9 |

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information

Ecotoxicological effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number

080111 Waste paint and varnish containing organic solvents or other dangerous substances

Recommendation

Contaminated packaging

Waste key number

Recommendation

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

Additional information

SECTION 14: Transport information

14.1 UN number

1263

14.2 UN proper shipping name

| | |
|------------|------------------------|
| ADR, ADN | Paint related material |
| IMDG, IATA | PAINT RELATED MATERIAL |

14.3 Transport hazard class(es)

| | |
|----------|---|
| ADR, ADN | 3 |
| IMDG | 3 |
| IATA | 3 |

14.4 Packing group

III

14.5 Environmental hazards

| | |
|-------------------------|-----|
| Marine Pollutant - IMDG | Yes |
| Marine Pollutant - ADN | |

14.6 Special precautions for user

Land transport

| | |
|--------------------------------------------|----------------------------|
| Code: ADR/RID | F1 |
| Kemmler-number | 30 |
| Hazard label ADR | 3 |
| Limited quantities | 5L |
| Contaminated packaging: Instructions | P001 - IBC03 - LP01 - R001 |
| Contaminated packaging: Special provisions | PP1 |
| Special provisions for packing together | MP19 |
| Portable tanks: Instructions | T2 |
| Portable tanks: Special provisions | TP1 - TP29 |
| Tank coding | LGBF |
| Tunnel restriction | D/E |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

| | | | |
|-------------|----------------|-------------|----------|
| Article No. | | Issue date: | 23.01.18 |
| Version | 6 (23.01.18) | Page | 7 / 9 |

| | |
|--------------------|-----------------|
| Remarks | |
| EQ | E1 |
| Special provisions | 163 - 367 - 650 |

Inland waterway craft

| | |
|---------------------|--|
| Hazard label | |
| Limited quantities | |
| Transport permitted | |
| Equipment necessary | |
| Ventilation | |
| Remarks | |
| EQ | |
| Special provisions | |

Sea transport

| | |
|--------------------------------------------|-----------------------|
| EmS | F-E, S-E |
| Special provisions | 163 - 223 - 367 - 955 |
| Limited quantities | 5L |
| Contaminated packaging: Instructions | P001 - LP01 |
| Contaminated packaging: Special provisions | PP1 |
| IBC: Instructions | IBC03 |
| IBC: Provisions | - |
| Tank instructions IMO | - |
| Tank instructions UN | T2 |
| Tank instructions Special provisions | TP1 - TP29 |
| Stowage and segregation | category A |
| Properties and observations | |
| Remarks | |
| EQ | E1 |

Air transport

| | |
|----------------------|------------------|
| Hazard | Flammable Liquid |
| Passenger | 355 (60L) |
| Passenger LQ | Y344 (10L) |
| Cargo | 366 (220L) |
| ERG | 3L |
| Remarks | |
| EQ | E1 |
| Special Provisioning | A192 |

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Europe

Contents of VOC [%]

Contents of VOC

[g/L]

Further regulations, limitations and legal requirements

Germany

Storage class

Water Hazard Class

non hazardous to water

WGK catalog number

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

| | | | |
|-------------|----------------|-------------|----------|
| Article No. | | Issue date: | 23.01.18 |
| Version | 6 (23.01.18) | Page | 8 / 9 |

Incident regulation
Information on working limitations
Further regulations, limitations and legal requirements

Denmark

Further regulations, limitations and legal requirements

Hungary

Further regulations, limitations and legal requirements

Great Britain

Further regulations, limitations and legal requirements

Switzerland

Contents of VOC [%]

65 - 68 %

Further regulations, limitations and legal requirements

USA

Further regulations, limitations and legal requirements
Federal Regulations
State Regulations

Japan

Further regulations, limitations and legal requirements

Canada

Further regulations, limitations and legal requirements

15.2 Chemical Safety Assessment

SECTION 16: Other information

Further information

Hazard statements (CLP)

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Further information

This information is based on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

Literature

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Reason of change

Additional information

